



BUILDING PRODUCT INFORMATION SHEET

Weathertex Primelok Cladding

Effective June 2024

Designated building product class

Class 1

Product Description

Weathertex Primelok cladding is an exterior weatherboard system made from Australian hardwood fibre. It features horizontal weatherboards and includes additional accessories such as anodized aluminium internal and external corners and polycarbonate ABS joiners. The weatherboards are 9.5 mm thick, cut from exterior-grade wood fibre-based panels. These fibres, sourced from selected Australian hardwoods, are pre-treated with steam under pressure and bonded using natural lignins present in the fibres. To minimize moisture absorption, the weatherboards contain a waterproofing agent. Available in both smooth and textured finishes (Ruff-Sawn and Woodsman), the boards can be either primed or left natural and uncoated. The standard length of each board is 3660 mm, with various widths depending on the profile. The Primelok weatherboards also feature a polycarbonate angled spline at the rear, ensuring correct alignment and overlap during installation.

Key Technical Specifications

Specification	Details
Length	3660mm (2745 and 2440mm in some profiles)
Thickness	9.5mm
Width	170 or 200mm

Place of Manufacture

Legal Name	Weathertex PTY Ltd
Address	470 Masonite Road, Heatherbrae, NSW 2324 Australia
Website	www.weathertex.com.au
Email	sales@weathertex.com.au
Phone	+61 1800 040 080

New Zealand importer/distributor

Legal Name	ITI NZ Ltd
Address	26 Keeling Road, Henderson, Auckland 0612
Website	www.iti.net.nz
Email	sales@iti.net.nz
Phone	(09) 6200260
NZBN	326102

Contribution to Building Work Code Obligations

Building Clause	Relatability	Supporting Information
Clause B1 Structure	Performance B1.3.1, B1.3.2, B1.3.4, B1.3.3(a), (f), (h), (j), (q).	Weathertex Cavity fixed sheet cladding systems meet the requirement for loads arising from self-weight, seismic activity, wind, and creep.
Clause B2 Durability	Performance B2.3.1(b) 15 Years, B2.3.1(c) 5 Years and B2.3.2	Weathertex cavity fixed cladding systems meet performance requirements of this clause of a minimum 15 years for the weatherboards and flashings and 5 years for the paint finish system.

Document Name	Product	Version	Issued Date:	Review Date:	Reviewed by:	Approved by:
Building Product Information Sheet	Weathertex Primelok Cladding	1	May 2024	May 2025		Director

Clause E2 External Moisture	Performance E2.3.2	Weathertex cladding systems are designed as an external cladding system as a first line of defiance against the ingress of external moisture.
Clause F2 Hazardous Building Materials	Performance F2.3.1	Weathertex cladding systems contain no harmful chemical treatments or toxic components.

Scope of Use

- Suitable for exterior cladding on residential and light commercial buildings in New Zealand.
- Applicable for use on timber or steel-framed buildings.
- Must be installed according to the Weathertex New Zealand Installation Manual.
- Conforms to New Zealand Building Code Acceptable Solution E2/AS1 and NASH Building Envelope Solutions.

Limitations on Use

- Weathertex Primelok weatherboard cladding must be installed in accordance with the requirements of the Weathertex New Zealand installation manual.
- Weathertex Primelok must be installed horizontally on flat surfaces by trade qualified or LBP registered personnel.
- Weathertex can be installed on buildings in NZ, situated in wind zones up to and including Extra High, and with a risk score of 0-20 calculated in accordance with NZBC Clause E2/AS1.

Design Requirements

- Weathertex cladding system are designed for use as an exterior cladding on residential and light commercial building in New Zealand.
- Weathertex cladding systems can be installed on timber or steel framed buildings, in accordance with NZBC Acceptable Solution E2/AS1 and NASH Building Envelope Solutions.

Installation Requirements

- Weathertex cladding system must be installed in accordance with the requirements of the Weathertex New Zealand Installation manual.

Maintenance Requirements

- Weathertex cladding system must be maintained in accordance with the selected coating manufacturer's requirements. See also the coating and maintenance clauses and requirements outlined in the Weathertex New Zealand installation manual.

Supporting Documentation

Document	Description	Link
Safety Data Sheet	Detailed safety information for Weathertex products.	Click here
Installation Manual	Step-by-step installation guides and visual demonstrations for Weathertex products.	Click here
Technical Brochures	Comprehensive technical specifications for Weathertex products.	Click here

Document Name	Product	Version	Issued Date:	Review Date:	Reviewed by:	Approved by:
Building Product Information Sheet	Weathertex Primelok Cladding	1	May 2024	May 2025		Director